

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Disclosure Document Deposit Request

Mail to:

Box DD
Assistant Commissioner for Patents
Washington, DC 20231

Inventor(s): Gregory J. Mclemore

Title of Invention: Mclemore Personal Fragrance Specialty Display Shelf

Enclosed is a disclosure of the above-titled invention consisting of _____ sheets of description and 2 sheets of drawings. A check or money order in the amount of 385.00 is enclosed to cover the fee (37 CFR 1.21(c)).

The undersigned, being a named inventor of the disclosed invention, requests that the enclosed papers be accepted under the Disclosure Document Program, and that they be preserved for a period of two years.

Gregory J. Mclemore
Signature of Inventor

204 Madison st
Address

Gregory J. Mclemore
Typed or printed name

7/10/03
Date

Franklin VA. 23851
City, State, Zip

NOTICE OF INVENTORS

It should be clearly understood that a Disclosure Document is not a patent application, nor will its receipt date in any way become the effective filing date of a later filed patent application. A Disclosure Document may be relied upon only as evidence of conception of an invention and a patent application should be diligently filed if patent protection is desired.

Your Disclosure Document will be retained for two years after the date it was received by the United States Patent and Trademark Office (USPTO) and will be destroyed thereafter unless it is referred to in a related patent application filed within the two-year period. The Disclosure Document may be referred to by way of a letter of transmittal in a new patent application or by a separate letter filed in a pending application. Unless it is desired to have the USPTO retain the Disclosure Document beyond the two-year period, it is not required that it be referred to in the patent application.

The two-year retention period should not be considered to be a "grace period" during which the inventor can wait to file his/her patent application without possible loss of benefits. It must be recognized that in establishing priority of invention an affidavit or testimony referring to a Disclosure Document must usually also establish diligence in completing the invention or in filing the patent application since the filing of the Disclosure Document.

If you are not familiar with what is considered to be "diligence in completing the invention" or "reduction to practice" under the patent law or if you have other questions about patent matters, you are advised to consult with an attorney or agent registered to practice before the USPTO. The publication, *Attorneys and Agents Registered to Practice Before the United States Patent and Trademark Office*, is available from the Superintendent of Documents, Washington, DC 20402. Patent attorneys and agents are also listed in the telephone directory of most major cities. Also, many large cities have associations of patent attorneys which may be consulted.

You are also reminded that any public use or sale in the United States or publication of your invention anywhere in the world more than one year prior to the filing of a patent application on that invention will prohibit the granting of a patent on it.

Disclosures of inventions which have been understood and witnessed by persons and/or notarized are other examples of evidence which may also be used to establish priority.

There is a nationwide network of Patent and Trademark Depository Libraries (PTDLs), which have collections of patents and patent-related reference materials available to the public, including automated access to USPTO databases. Publications such as *General Information Concerning Patents* are available at the PTDLs, as well as the USPTO's Web site at www.uspto.gov. To find out the location of the PTDL closest to you, please consult the complete listing of all PTDLs that appears on the USPTO's Web site or in every issue of the Official Gazette, or call the USPTO's General Information Services at 800-PTO-9199 (800-786-9199) or 703-308-HELP (703-308-4357). To insure assistance from a PTDL staff member, you may wish to contact a PTDL prior to visiting to learn about its collections, services, and hours.



E-6000[®] is a registered trademark in the United States.
Made in the U.S.A. by Eclectic Products, Inc., Pineville, LA 71361.

E-6000

For technical assistance visit www.tech@edecticproducts.com
or call (800) 767-4667.

TECHNICAL DATA SHEET**E-6000[™] INDUSTRIAL STRENGTH****PRODUCT DESCRIPTION**

E-6000 is a unique, adhesive formulated to meet high-performance industrial requirements. E-6000 has exceptional adhesion to wood, metal, glass, fiberglass, ceramics, masonry and concrete. It also adheres strongly to leather, rubber, vinyl and many plastics. E-6000 maintains its flexible bond in cold temperatures and may be used to bond items subject to vibration. The clear E-6000 is not formulated for exposure to sunlight. For these applications, paint over E-6000 after it has cured or try UV-6800[™] adhesive specially formulated for outdoor use.

PRODUCT CHARACTERISTICS & BENEFITS

Flexible	Does not become brittle in cold weather; can bond items subject to vibration
Waterproof	Can be submerged in fresh and salt water after complete cure
Non-flammable	
Paintable	Paint to match surrounding area or make UV-resistant
Chemical resistant	Safe for applications exposed to dilute acids and dilute caustics

PROPERTIES OF UNCURED MATERIAL

Density	11.1 lbs/gal
Solids	30% by weight, 40% by volume
Viscosity	High: 200,000 cps; Medium: 100,000 cps; Low: 50,000 cps
Solvent	Perchloroethylene (non-flammable)
Tack time	5 minutes
Color	Clear, white, gray, black
Shelf life	1 year (unopened)
Full cure time	Thin film: 24 hours; Thick film: 48-72 hours
VOC	1.198 grams/liter
Freeze/thaw stability	Stable; allow product to warm to room temperature before using.
Storage	Store in dry area between 50°F (10°C) and 80°F (27°C).

**33433**

PATENT TRADEMARK OFFICE

PROPERTIES OF CURED MATERIAL

Hardness	80A
Tensile strength	3500 lb/in ² (ASTM D-412)
Elongation	900% (ASTM D-412)
Chemical resistance	Excellent to water, dilute acids and dilute bases
Service temperature range	-40°F (-40°C) to 150°F (66°C)
Paint-over time	24 hours
UV resistance	None; paint over E-6000 or use UV-6800 [™]
Dielectric strength	400V/mil (ASTM D-149). This is the maximum voltage that can be applied to a given material without causing it to break down.

ADHESION TEST: Average values, 180° peel, 7-day cure per ASTM D-903

Glass	40 pli	PVC	27 pli	Wood	29 pli	Urethane	32 pli	Aluminum	30 pli
Leather	20 pli	Steel	25 pli	Cement/Brick	25 pli	ABS	32 pli	Acrylic	36 pli
Rubber	30 pli	Neoprene	32 pli	Polycarbonate	37 pli	Tile	25 pli		